

**GLOSS CAST COATED 80gsm – REMOVABLE
KRAFT 85 GSM**

Issue: 14/10/2011
Modification:2
page 1/1

GENERAL PRODUCT CHARACTERISTICS

Total weight	183 gsm ± 5%	ISO 536
Total caliper	189 µm ± 7%	ISO 534

FACE

White gloss cast coated woodfree paper

Substance	80 gsm ± 4	ISO 536
Caliper	89 µm ± 5	ISO 534

ADHESIVE

Water emulsion removable adhesive type. Good short and long-term removability from most substrates including treated cardboard, glass, steel and polyolefins

Peel adhesion	0,6 N/inch ± 0,2	FINAT1
Shear test	6h ± 2	FINAT8
Quick stick	0,7 N/inch ± 0,2	FINAT9
Min. application temp.	-5°C / +50°C	
Service temp. Range	-20°C/+60°C	

BACKING

One-side coated white kraft, solventless silicon coated

Substance	85 gsm ± 3	ISO 536
Caliper	87 µm ± 5	ISO 534

SAFETY REGULATIONS

- The self-adhesive product meets the European Standard EN71-3:2013 "Safety of Toys" - Migration of certain elements

APPLICATIONS

Top-quality multicolour labels, good print definition and finishing. Prestigious promotional labelling.

NB. the removing properties are influenced by the kind of application surface.

Trials are recommended, by the purchaser, prior to use, to determine the suitability of the product to the intended substrate.

Not suitable for application on paper surfaces, particularly coated and varnished papers.

PRINTABILITY

Face: excellent printing results by all common print processes, particularly using brilliant inks.

Backing: good printing results by all common print processes, in one or more colors.

ON REQUEST

- Splits on the release paper, standard spacing 38mm or customized.
- Material certified Forest Stewardship Council (FSC)

SHELF LIFE AND USE

Two (2) years from delivery date when stored at the following conditions:

- Temperature +5°C/+35°C
- Relative Humidity 45% - 60%
- Store in a cool dry place
- Store away from heaters or direct sunlight or rain
- Keep the sheets flat, the reels piled
- Store in the original packaging, remove packaging just before use
- Material to be acclimatized at least 24 hrs to ambient conditions

All ITALSTICK products are subject to careful quality control throughout the production process and are warranted to be free from manufacturing defect and of quality. The reported information is based upon research and tests the Company believes to be reliable; such information does not constitute a warranty. The purchaser and/or user should carefully test, prior to use, suitability and performance of the product for the intended use and shall assume all risks for such use. ITALSTICK shall not be liable for damages beyond the replacement value of the defected product nor for incidental or consequential damages

All technical data are subject to change without prior notice.

ITALSTICK Soc. Coop.
via della Stazione, 6
I-41019 Soliera
www.italstick.com

Ph. +39 059 566705
Fax +39 059 565127
info@italstick.com