

SEMI-GLOSS MC 80gsm – SUPERTACK - KRAFT K85

Issue: 17/11/2011
Modification:3
page 1/1

GENERAL PRODUCT CHARACTERISTICS

Total weight	185 gsm ± 5%	ISO 536
Total caliper	168 µm ± 6%	ISO 534

FACE

White semi-gloss coated woodfree paper

Substance	80 gsm ± 2	ISO 536
Caliper	66 µm ± 2	ISO 534

ADHESIVE

Water emulsion acrylic based Supertack type, high initial tack and strong permanent bond for general use. Recommended on a wide variety of substrates, including paper, board, glass, steel

Peel adhesion	16.5/inch ± 2	FINAT1
Shear test	4h ± 2	FINAT8
Quick stick	14.4 N/inch ± 4	FINAT9
Min. application temp.	+5°C /+40°C	
Service temp. Range	-20°C/+90°C	

BACKING

One-side coated white kraft, solventless silicon coated

Substance	85 gsm ± 3	ISO 536
Caliper	87 µm ± 5	ISO 534

SAFETY REGULATIONS

- The self-adhesive product meets the European Standard EN71-3:2013 "Safety of Toys" - Migration of certain elements
- The adhesive coating meets the FDA 21 CFR 175.105 for contact with foodstuffs

APPLICATIONS

Labelling on different substrates, promotion campaign, children activity books, cosmetic and pharma industry. Suitable for application on curved surfaces, small to medium diameter.

Trials are recommended, by the purchaser, on the intended substrates, prior to use, for product suitability.

PRINTABILITY

Face: excellent printing results by all common print processes, particularly using brilliant inks.

Backing: good printing results by all common print processes, in one or more colors.

ON REQUEST

- Splits on the release paper, standard spacing 38mm or customized.
- Material certified Forest Stewardship Council (FSC)

SHELF LIFE AND USE

Three (3) years from delivery date when stored at the following conditions:

- Temperature +5°C/+35°C
- Relative Humidity 45% - 60%
- Store in a cool dry place
- Store away from heaters or direct sunlight or rain
- Keep the sheets flat, the reels piled
- Store in the original packaging, remove packaging just before use
- Material to be acclimatized at least 24 hrs to ambient conditions

All ITALSTICK products are subject to careful quality control throughout the production process and are warranted to be free from manufacturing defect and of quality. The reported information is based upon research and tests the Company believes to be reliable; such information does not constitute a warranty. The purchaser and/or user should carefully test, prior to use, suitability and performance of the product for the intended use and shall assume all risks for such use. ITALSTICK shall not be liable for damages beyond the replacement value of the defected product nor for incidental or consequential damages

All technical data are subject to change without prior notice.

ITALSTICK Soc. Coop.
via della Stazione, 6
I-41019 Soliera
www.italstick.com

Ph. +39 059 566705
Fax +39 059 565127
info@italstick.com