

**OPP WHITE MATT CAVITATED 70  $\mu$ m – PERMANENT –  
KRAFT 135gsm**

Issue: 27/05/2016  
Modification: 2  
page 1/1

**GENERAL PRODUCT CHARACTERISTICS**

Total weight	201 gsm $\pm$ 6%	ISO 536
Total caliper	220 $\mu$ m $\pm$ 7%	ISO 534

**FACE:**

Bi-axially oriented polypropylene film, excellent opacity, cavitated, white matt, static resistant coated

Substance	49 gsm $\pm$ 3	-
Caliper	77 $\mu$ m $\pm$ 5	-

**ADHESIVE**

Water emulsion acrylic based permanent type, for application on a wide variety of surfaces such as paper, glass, steel.

Peel adhesion	9.8/inch $\pm$ 1	FINAT1
Shear test	20h $\pm$ 5	FINAT8
Quick stick	6.9 N/inch $\pm$ 1	FINAT9
Min. application temp.	+5°C	
Service temp. Range	-15°C/+80°C	

**BACKING**

One-side coated white kraft, solventless silicon coated

Substance	135 gsm $\pm$ 7	ISO 536
Caliper	130 $\mu$ m $\pm$ 8	ISO 534

**SAFETY REGULATIONS**

The adhesive coating and backing paper meet the European Standard EN71-3:2013 "Safety of Toys" - Migration of certain elements

**APPLICATIONS**

Hi-quality labels for cosmetics, appliances and toys, furniture and vehicle industry. Promotional and decorative labels for indoor and outdoor use. Good dimensional stability and ageing resistance.

Trials are recommended, by the purchaser, prior to use, on the intended substrates for product suitability.

**PRINTABILITY**

Face: screen-and flexo printing, conventional and UV- offset printing using suitable inks. Consult your inks supplier about suitable printing inks to obtain maximum ink bonding

Backing: good printing results by all common print processes, in one or more colors

**ON REQUEST**

Forest Stewardship Council certified backing material.

Splits on the release paper, standard spacing 38mm or customized.

**SHELF LIFE AND USE**

Two (2) years from delivery date when stored at the following conditions:

- Temperature +5°C/+35°C.
- Relative Humidity 45% - 60%.
- Store in a cool dry place.
- Store away from heaters or direct sunlight or rain.
- Keep the sheets flat, the reels piled.
- Store in the original packaging.  
Store in the original packaging, remove packaging just before use.
- Material to be acclimatized at least 24 hrs to ambient conditions.