

## RECYCLING PAPER WHITE 80gsm – PERMANENT – KRAFT 85gsm

Issue: 03/05/2011  
Last Modification: 15/03/2022  
Revision: 8  
page 1/1

### GENERAL PRODUCT CHARACTERISTICS

Total weight	183 gsm ± 5%	ISO 536
Total caliper	206 µm ± 5%	ISO 534

### FACE

Recycled white uncoated paper, environmental paper, 100% from post-consumer recycled fibres.

Substance	80 gsm ± 3	ISO 536
Caliper	104 µm ± 3	ISO 534

### ADHESIVE

Water emulsion acrylic based permanent type, for application on a wide variety of surfaces such as paper, glass, steel.

Peel adhesion	15.7/inch ± 2	FINAT1
Shear test	4h ± 2	FINAT8
Quick stick	13.7 N/inch ± 4	FINAT9
Application temp. Range	+5°C / +40°C	
Service temp. Range	-15°C / +80°C	

### BACKING

One-side coated white kraft, solventless silicon coated.

Substance	85 gsm ± 3	ISO 536
Caliper	87 µm ± 5	ISO 534

### SAFETY REGULATIONS

- Face: EU Ecolabel certified, Austrian Ecolabel  
Meets the criteria for EN12281, DIN6738 and ISO 20494
- Adhesive coating and Support: meet the European Standard EN71-3:2018 "Safety of Toys / Migration of certain elements"

### APPLICATIONS

Self-adhesive complex made from 100% post-consumer recycled fibres. The product is particularly suitable for initiatives that contemplate environmental protection without sacrificing the characteristics of a common self-adhesive complex. Suitable for publications, inserts and covers, environmental bulletins, labelling on recycled materials.

Trials are recommended, by the purchaser, on the intended substrates, prior to use, for product suitability.

### PRINTABILITY

Face: excellent printing results by all common print processes, particularly using brilliant inks.  
Backing: good printing results by all common print processes, in one or more colours.

### ON REQUEST

- Splits on the release paper, standard spacing 38mm or customized.
- Material certified Forest Stewardship Council® FSC-C107414

### SHELF LIFE AND USE

- One (1) year from delivery date when stored at the following conditions:
- Temperature +5°C/+35°C
  - Relative Humidity 45% - 60%
  - Store in a cool dry place
  - Store away from heaters or direct sunlight or rain
  - Keep the sheets flat, the reels piled
  - Store in the original packaging, remove packaging just before use
  - Material to be acclimatized at least 24 hours to ambient conditions