

**OFFSET BOARD 150 GSM – SUPERTACK –
KRAFT 85 GSM**
Forest Stewardship Council® FSC-C107414

Issue:31/03/2021
Last modification:-
Revision: 0
page 1/1

GENERAL PRODUCT CHARACTERISTICS

Total weight	259gsm ± 5%	ISO 536
Total caliper	272 µm ± 6%	ISO 534

FACE

White uncoated board, woodfree		
Substance	150 gsm ± 7	ISO 536
Caliper	168 µm ± 8	ISO 534

ADHESIVE

Water emulsion acrylic based Supertack type, high initial tack and strong permanent bond for general use. Recommended on a wide variety of substrates, including paper, board, glass, steel

Peel adhesion	16.5/inch ± 2	FINAT1
Shear test	4h ± 2	FINAT8
Quick stick	14.4 N/inch ± 4	FINAT9
Min. application temp.	+5°C /+40°C	
Service temp. Range	-20°C/+90°C	

BACKING

One-side coated white kraft, solventless silicon coated		
Substance	85 gsm ± 3	ISO 536
Caliper	87 µm ± 5	ISO 534

SAFETY REGULATIONS

- The self-adhesive product meets the European Standard EN71-3:2018 "Safety of Toys" - Migration of certain elements Material certified Forest Stewardship Council® FSC-C107414
- The adhesive coating meets the FDA 21 CFR 175.105 "Adhesives"

APPLICATIONS

Identification labels, postcards and promotional tags . Any applications where high stiffness and thickness are required.

Trials are recommended, by the purchaser, on the intended substrates, prior to use, for product suitability.

PRINTABILITY

Face: excellent printing results by all common print processes
Backing: good printing results by all common print processes, in one or more colors.

ON REQUEST

- Splits on the release paper, standard spacing 38mm or customized.

SHELF LIFE AND USE

One (1) year from delivery date when stored at the following conditions:

- Temperature +5°C/+35°C
- Relative Humidity 45% - 60%
- Store in a cool dry place
- Store away from heaters or direct sunlight or rain
- Keep the sheets flat, the reels piled
- Store in the original packaging, remove packaging just before use
- Material to be acclimatized at least 24 hrs to ambient conditions