

**OFFSET UNCOATED PAPER 80gsm – REMOVABLE -  
KRAFT 85GSM**

Issue: 17/07/2013  
Modification:2  
page 1/1

**GENERAL PRODUCT CHARACTERISTICS**

Total weight	183 gsm ± 6%	ISO 536
Total caliper	204 µm ± 6%	ISO 534

**FACE**

White uncoated paper, woodfree, high whiteness and opacity

Substance	80 gsm ± 4	ISO 536
Caliper	104 µm ± 4	ISO 534

**ADHESIVE**

Water emulsion removable adhesive type, good short and long-term removability from most substrates including processed board, glass, steel and polyolefin films.

Peel adhesion	0.6 N/inch ± 0.2	FINAT1
Shear test	6h ± 2	FINAT8
Quick stick	0.7 N/inch ± 0.2	FINAT9
Min. application temp.	-5°C / +50°C	
Service temp. Range	-20°C/+60°C	

**BACKING**

One-side coated white kraft, solventless silicon coated

Substance	85 gsm ± 3	ISO 536
Caliper	87 µm ± 5	ISO 534

**SAFETY REGULATIONS**

The self-adhesive product meets the European Standard EN71-3:2013 "Safety of Toys" - Migration of certain elements

**APPLICATIONS**

All types of labels for industrial applications, information and product labeling.

NB. the removing properties are influenced by the kind of application surface. Trials are recommended, by the purchaser, prior to use, on the intended substrates.

Not suitable for application on paper surfaces.

**PRINTABILITY**

Face: excellent printing results by all common print processes, particularly using brilliant inks.

Backing: good printing results by all common print processes, in one or more colors.

**ON REQUEST**

- Splits on the release paper, standard spacing 38mm or customized.
- Material certified Forest Stewardship Council

**SHELF LIFE AND USE**

One (1) year from delivery date when stored at the following conditions:

- Temperature +5°C/+35°C
- Relative Humidity 45% - 60%
- Store in a cool dry place
- Store away from heaters or direct sunlight or rain
- Keep the sheets flat, the reels piled
- Store in the original packaging, remove packaging just before use
- Material to be acclimatized at least 24 hrs to ambient conditions

All ITALSTICK products are subject to careful quality control throughout the production process and are warranted to be free from manufacturing defect and of quality. The reported information is based upon research and tests the Company believes to be reliable; such information does not constitute a warranty. The purchaser and/or user should carefully test, prior to use, suitability and performance of the product for the intended use and shall assume all risks for such use. ITALSTICK shall not be liable for damages beyond the replacement value of the defected product nor for incidental or consequential damages

All technical data are subject to change without prior notice.

**ITALSTICK Soc. Coop.**  
via della Stazione, 6  
I-41019 Soliera  
www.italstick.com

Ph. +39 059 566705  
Fax +39 059 565127  
info@italstick.com