

WHITE OFFSET 80gsm – SUPERTACK PLUS – KRAFT 85gsm

Issue: 07/11/2013
Modification: 0
page 1/1

GENERAL PRODUCT CHARACTERISTICS

Total weight	187gsm ± 7%	ISO 536
Total caliper	206µm ± 6%	ISO 534

FACE

White woodfree uncoated paper, high whiteness and opacity

Substance	80gsm ± 4	ISO 536
Caliper	104µm ± 4	ISO 534

The product meets the European Toy Regulation EN-71 part 3 “Migration of Certain Elements/Application on Toys”

ADHESIVE

Water emulsion, styrene-butadiene based Extra - Permanent type, high tack. Good adhesion on a wide variety of surfaces such as paper, board, glass, steel and plastics. Recommended for applications where a high initial tack is required

Peel adhesion	17.5 N/inch ±2	FINAT1
Shear test	7h ± 3	FINAT8
Quick stick	15.5 N/inch ± 4	FINAT9
Min. application temp.	+5°C / +40°C	
Service temp. Range	-15°C/+80°C	

BACKING

One-side coated white kraft; solventless silicon coated

Substance	85 gsm ± 3	ISO 536
Caliper	87 µm ± 5	ISO 534

The product meets the European Toy Regulation EN-71 part 3 “Migration of Certain Elements/Application on Toys”

APPLICATIONS

All types of labels for industrial applications: information and product labeling.

PRINTABILITY

Face: good printing results by all common print processes; suitable for laser and ink-jet printing
Backing: good printing results by all common print processes, in one or more colors.

SHELF LIFE AND USE

One (1) year from delivery date when stored at the following conditions:

- Temperature +5°C/+35°C
- Relative Humidity 45% - 60%
- Store in a cool dry place away from heaters or direct sunlight or rain
- Keep the sheets flat, the reels piled
- Store in the original packaging